

# G15

Mixer

**PMES**  
PUMP- MISCH- FÖRDERSYSTEME GMBH



## The lightweight electric driven continuous mixer G15 for mixing of dry mortar

The general purpose continuous mixer G15 is equipped with a small 1.1kW electric drive. It works perfect with materials up to 3mm grain size.

A small but productive continuous mixer for all kind of preblended dry mortars in bags.

Due to the low weight and foldable chassis the G15 is easy to transport and to set up.



# G15

Mixer

## ► Fields of application

The G15 is a tiny and mobile electric driven continuous mixer. This automatic mixing unit is working with any light dry mortar in bags. Whether it is lime-cement or cement mortar, filler or skim coat, levelling compound, reinforcement or bonding mortar, finish and decoration plaster, etc., all materials up to 3mm grain size will be continuously mixed with water for manually use or to feed a mortar pump for professional and efficient processing.

## ► Function

Just connect the G15 with a water hose and with an electric supply. Open dry mortar bags to fill the hopper and press the start button. The drive activates the dosing shaft inside the dry material hopper with a positive locked mixing shaft inside the mixing tube. The dosing shaft provides a constant flow of dry mortar into the mixing tube and an adjustable water metering device adds water and allows to set up the consistency of the wet mix. The paddles of the rotating mixing shaft prepare a homogeneous mortar until you stop the whole process by pushing the stop button.

## ► Advantages

The G15 is equipped with a 230V drive that can be even disassembled for transport. With the flexible output range it matches to many applications and job site conditions.

The whole unit is foldable. This makes it easy to handle - it can be pushed like a wheelbarrow. It is a small handsome unit, attractive by its simplicity. Snap closings provide access to clean the mixing shaft or mixing tube and to dismantle the parts for easy transport. The whole mixing tube is made of rubber for less mortar adhesion and quick cleaning, furthermore it ensures a longer lifetime.

A comprehensive range of accessories are available to equip the G15

For instance electric cables in different length, water hoses, couplings, a water booster pump, water filters, etc. Please contact us for details.

## ► Technical data G15

Power supply	1~230V/50Hz
Output	15 - 20l/min
Electric motor	1.1kW
Hopper volume	80l
Water connection	Geka 1/2"
Water input pressure	>2.5bar
Weight	67kg
Dimensions LxWxH	1500x650x900mm
Part no.	500040

Standard equipment: documentation



[www.pmfsgmbh.de](http://www.pmfsgmbh.de)